

CK 315 C

7000071


- Duct fan with circular connections.
- Proven performance and reliability.
- Compact with high capacity and efficiency.
- Low sound levels.
- Impeller with backward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings.
- Integrated motor protection.
- Junction box has enclosure class IP 54.

- For speed control a transformer or electronic speed controller can be connected.
- Fan housing is manufactured from galvanized sheet steel.
- The fan is intended to be installed in a duct system.
- When duct connected the fan can be installed outside or in damp environments.
- Easy installation in any position.




This product is not sold within the EU.


PRESSURE/FLOW



POWER/FLOW



SFP



TECHNICAL DATA

Voltage	230 V
Frequency	50 Hz
Phase	1 ~
Current	1.18 A
Power	269 W
Speed	2550 r.p.m.
Capacitor	8 µF
Max. temp of transported air	60 °C
Sound pressure level, 3 m	47 dB(A)
Weight	6.0 kg
Wiring diagram	4040001

ACCESSORIES

- Mounting bracket Kit MB
- Mounting clamp MK 315
- Safety grille BSV 315
- Back draught shutter RSK 315
- Louvre YG 315
- Louvre shutter VK 315
- Filterbox FLK 315
- Filterbox FLF 315
- Silencer LDC 315
- Transformer controller VRTE 1
- Transformer controller VRDE 1.5
- Speed controller VRS 2.0

SOUND DATA

	L_{WA} tot dB (A)	63	125	250	500	1K	2K	4K	8K
5.Surrounding 230 V	54	32	40	41	46	46	52	42	34
5.Outlet 230 V	78	56	60	64	70	71	73	70	70
5.Inlet 230 V	77	53	60	64	67	67	72	70	71
4.Inlet 165 V	73	49	56	61	63	63	69	65	66
3.Inlet 135 V	66	46	52	57	56	57	61	61	51
2.Inlet 110 V	59	41	47	51	50	51	53	53	40
1.Inlet 80 V	49	35	42	42	41	42	42	34	31

TRANSFORMER STEPS

1. 80 V 2. 110 V 3. 135 V 4. 165 V 5. 230 V

MORE INFORMATION



Find out the latest updated information about this product by visiting www.ostberg.com or by scanning QR code.

DIMENSIONS (mm)

